



**NOTE:**

1. CABLE: 32AWG,UL20276,AL+D-FOIL,[(#32\*1P+D+FAM)\*5PCS+#32\*4C], BLACK COLOR,OD=3.8±0.2mm,PVC JACKET\*1PC.
2. LENGTH:L.
3. CONNECTORS: HDMI19P(M)\*1PCS,MICRO HDMI19P(M)(BLACK INSULATOR)(SHELL GOLD PLATED).
4. MOLD: ASS'Y Iphone TYPE.
5. CONTACTS:
 

HDMI(M)	1	3	2	4	6	5	7	9	8	10	12	11	14	19	17	13	15	16	18	64
Micro HDMI	3	5	4	6	8	7	9	11	10	12	14	13	2	1	16	15	17	18	19	64
	PAIR		G	PAIR		G	PAIR		G	PAIR		G	PAIR		G	4C				SHELL
6. Test machine test condition.
  - A.100% OPEN,SHORT&INTERMITTANCE TEST.
  - B.CONDUCTOR RESISTANCE: 3ohms MAX:
  - C.INSULATION RESISTANCE: 5M Min/,10ms:
7. ALL MUST BE MEET ON ROHS COMPLIANT.

COMPANY	2D		ITEM NO.	CH0048	NO	B6113	Part Name	HDMI M-MICRO HDMI APPLE HDMI REV1.4	SCALE	
REVISION	DATE	DISCRPTION	DRAWN BY						UNIT(mm)	
REV.A/0	2011.12.15	T6-1112013	DESIGNED BY				spec			
			APPROVAL BY						PAGE	1/1