


Universal Distribution Loose Tube CST Multimode Cable up to 24 Fibres



Universal Loose tube corrugated steel tape (CST) armoured optical fibre cables have been designed specifically for applications requiring a high degree of mechanical protection, including direct burial. These compact cables are extremely rugged, provide rodent resistance and are quick and easy to install.

Features

- Sequentially Metre Marked
- Internal/External Grade
- LSOH Black Sheath
- Corrugated Steel Tape Armour
- Bend Insensitive
- Duct Grade
- Rodent Resistant
- CPR compliant to Eca
- Cut to length service

Standards

ISO 11801-1, EN 50173-1:2002, IEC 60794-1

Flame Resistance

LSHF (LSOH): IEC 60332-1-2; IEC 60754-1, IEC 60754-2; IEC 61034-2; Class Eca

Construction

Loose Tube	ø2.8mm gel-filled loose tube with 2-24 fibres		
Fibre Colour Code	1	Red	13 Red w/mark every 70mm
	2	Green	14 Green w/mark every 70mm
	3	Blue	15 Blue w/mark every 70mm
	4	Yellow	16 Yellow w/mark every 70mm
	5	White	17 White w/mark every 70mm
	6	Grey	18 Grey w/mark every 70mm
	7	Brown	19 Brown w/mark every 70mm
	8	Violet	20 Violet w/mark every 70mm
	9	Turquoise	21 Turquoise w/mark every 70mm
	10	Black	22 White w/mark every 35mm
	11	Orange	23 Orange w/mark every 70mm
	12	Pink	24 Pink w/mark every 70mm
Strength Member	E- Glass yarns		
Armouring	0.15mm corrugated steel tape		
Sheath	1.5mm, Black, UV stabilised, EN 50290-2-27		
Sheath Marking	EXAMPLE: *METRE MARKED* - FASTFIBRE OPTICAL FIBRE CABLE STAM308B-KLSZHEF 8 FIBRE CST OM3 50/125 ECA *BATCH NUMBER* *WEEK/YEAR*		

Universal Distribution Loose Tube CST Multimode Cable up to 24 Fibres

Physical Properties

Attribute	IEC 60794-1-21/22 Method	Limits	
Nominal Diameter [mm]	-	2-24 fibres: 8.5mm	
Nominal Weight [kg/km]	-	2-24 fibres: 75kg/km	
Tensile Strength (dynamic)	E1	3000 N (fibre strain ≤ 0.6%)	
Tensile Strength (permanent)	E1	1000 N (fibre strain ≤ 0.2%)	
Crush (compressive strength)	E3	2200 N / 100mm	
Torsion	E7	5 cycles ± 1 Turn	
Kink	E10	The cables do not form a kink when a loop is drawn together to a diameter of 100mm	
Minimum bending Radius unloaded (permanent)	E11	R=85mm	
Minimum bending Radius loaded (installation)		R=170mm	
Temperature Range	F1	Operation Storage and Installation	-40°C to +70°C -40°C to +70°C
Heat of Combustion		2-24 fibres	1200 MJ/km 0.33 kWh/m

Ordering Information

Part Number	Description
STAM304BKLSZHEF	Internal/External Loose Tube Fibre CST Armoured Cable 4 Core OM3
STAM308BKLSZHEF	Internal/External Loose Tube Fibre CST Armoured Cable 8 Core OM3
STAM312BKLSZHEF	Internal/External Loose Tube Fibre CST Armoured Cable 12 Core OM3
STAM324BKLSZHEF	Internal/External Loose Tube Fibre CST Armoured Cable 24 Core OM3
STAM404BKLSZHEF	Internal/External Loose Tube Fibre CST Armoured Cable 4 Core OM4
STAM408BKLSZHEF	Internal/External Loose Tube Fibre CST Armoured Cable 8 Core OM4
STAM412BKLSZHEF	Internal/External Loose Tube Fibre CST Armoured Cable 12 Core OM4
STAM424BKLSZHEF	Internal/External Loose Tube Fibre CST Armoured Cable 24 Core OM4