



10/100/1000Base-T to 1000Base-SX, Incl. PSU SC connector, Up to 0.5km

The perfect converter solution for various fiber media

- Transforms wire based network media to fiber optic
- High quality and excellent reliability
- 10/100/1000Base-TX to 1000Base-SX
- Connectors: 1x RJ45, 1x SC Duplex
- Distance up to 0.5km
- Wavelength: 850nm
- Multimode Dual Fiber
- Automatic Cable detection - Auto MDI / MDI-X function
- Auto-Negotiation of Full- and half-duplex
- Diagnostic and monitoring LEDs for the status of power, link and act of the ports
- Suitable for 8.3/125 μ m, 8.7/125 μ m, 9/125 μ m or 10/125 μ m Fiber Cables
- Transmission Power: Minimum -17 dBm, Maximum -12 dBm
- Sensitivity Receiving Power: Minimum -20 dBm
- Supported Standards: IEEE 802.3 Ethernet, IEEE 802.3u Fast Ethernet, IEEE 802.3z Gigabit Ethernet
- 2MB Data Buffer
- Operating Temperature: 0 to 60°C
- Dimensions (L x W x H): 95mm x 70mm x 26mm
- Weight: 200g
- Standalone Converter with external power supply
- Input Supply Voltage: 5V DC



Package Content

- Media Converter
- Quick Installation Guide
- Power Adapter