

MODEL	BT5801WP-24G-4TC-BT
PRODUCT NAME	Full gigabit 4 optical 28 electric L2+ managed POE switch
Network port	24*10/100/1000M RJ45 PoE 4*10/100/1000M RJ45 4*100/1000M SFP
PoE Port	1-2 ports support IEEE802.3af/at/bt, with a maximum of 90W/port 3-24 ports support IEEE802.3af/at, with a maximum of 30W/port
Management Port	1 console port
Reset key	1
PoE power supply polarity	Af/at/bt: 12+ 45+ ; 36- 78- Af/at: 12+ 36-
PoE Power	400WMax.
CPU	500MHz
DDR	1G DDR3
FLASH	128MBytes
RAM	128MBytes
Bandwidth	56G/128Gbps
Packet forwarding	41.67Mpps
MAC Address	8K
Cache	4.1 Mbit SRAM Packet Buffer
Megaframe	10000Bytes
VLAN Address	4K
Transmission distance	10M: Cat3,4,5 UTP(≤250m) 100M : Cat5 or later UTP(150m) 1000M : Cat6 or later UTP(150m) SFP: Supports 1000M single-mode and multi-mode optical modules, with a maximum distance of ≤ 120km (depending on the optical module)
LED Indicator	PWR:Power indicator light SYS:System indicator lights 1-24:10/100、1000M Network connection indicator light 25-28:10/100、1000M Network connection indicator light
Power Adapter	AC: 100-240Vac 50-60Hz 5.1A 425WMax
Working temperature/humidity	-10~+55°C; 5%~90% Non solidification
Storage temperature/humidity	-40~+75°C; 5%~95% Non solidification
Product /Box (L*W*H)	440mm*290mm*45mm 515mm*375mm*95mm
N.W./G.W. (kg)	3.5kg/4.2kg
Lightning/surge protection level	6KV 8/20us; IP30
Installation method	Rack mounted (delivery rack ear accessories)
Certificates	3C; CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS;
Warranty	1 year of complete machine (excluding accessories)