

## DIGITUS Professional mini GBIC (SFP) Module, 1.25 Gbps, 0.55km



### Description

#### mini GBIC (SFP) Module, 1.25 Gbps, 0.55km

DIGITUS 1.25 Gbps SFP Module, Up to 550m Multimode, LC Duplex Connector 1000Base-SX, 850nm

The plug and play fiber connection

- The Plug & Play fiber optic link enables quick installation
- Sends data in high quality and additionally provides excellent reliability
- Distance up to 0,55km at a maximum data rate of 1.25Gbps
- Operating temperature: 0 °C ~ 70 °C

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

### Technical details

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, CISCO, D-Link, Edimax, Hirschmann, Intellinet, KTI Networks, Level One, Netgear, PLANET, Tenda, TP-Link, TRENDnet, ZyXEL, ZTE
- High quality and excellent reliability
- 1.25 Gbps Maximum Data Rate
- Compliant to IEEE 802.3z Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable
- Connector: 1x LC Duplex
- 1000Base-SX - For Short Haul
- Wavelength: 850nm
- Transmission power: minimum -8 dBm, maximum -3 dBm
- Sensitivity Receiving Power: Minimum -20 dBm
- For a Distance of up to 0.55km
- Suitable for 50/125µm and 62.5/125µm multimode fiber cables
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: 0 °C ~ 70 °C

### Package content

- SFP module