



Picture shows 6 way horizontal UK 1U PDU

- Horizontal UK 13A BS1363 outlets
- Tough 1U plastic ABS extrusion
- Shrouded switch with switch cover
- UK plug, or IEC C14 plug option
- 3-metre 1.5mm lead

The 1U horizontal plastic bodied PDUs are ideal for wall mounted cabinets, where weight is an important factor, and rack space is vital.

The cable exits the unit at the rear, making mounting of the PDU easy via the 2mm steel fixing brackets, surge options available.

Standard products

Order Code Product Description

H13A1U/6 Horizontal PDU with 6 x UK sockets, 3m lead to UK plug H13A1U/6/C14 Horizontal PDU with 6 x UK sockets, 3m lead to C14 plug

H13A1U/6/F Horizontal PDU with 6 x UK sockets, surge protection, 3m lead to UK plug H13A1U/6/F/C14 Horizontal PDU with 6 x UK sockets, surge protection, 3m lead to C14 plug

PDU technical data

Weight of PDU	0.65kg – 0.75kg
Net length of PDU	486mm
Net width of PDU	46mm
Net depth of PDU	46mm
Shipping length of PDU	538mm
Shipping Width of PDU	142mm
Shipping Depth of PDU	68mm
Shipping Weight of PDU	1kg – 1.1kg
Pack Size / Box quantity	1 / 10
PDU max power	3250W
Output rating	13A
Overall rating	16A
Input Frequency	50/60Hz
Acceptable Input Voltage	250VAC