

The power to connect



- Horizontal IEC C13 10A outlets
- Tough 1.5U aluminium extrusion
- Shrouded switch with switch cover
- C14, C20, Schuko, or 16A commando options
- 3-metre 1.5mm lead

Horizontal IEC PDUs are a popular unit when it comes to power distribution, as they allow a higher density of power sockets, to distribute power from one easy location in the rack.

The cable exits the unit at the rear, making mounting of the PDU easier, whilst taking up only 1.5U of vital rack space

Standard products

Order Code	Product Description
HIEC/4	4 way horizontal IEC C13 PDU with switch to 3m lead, UK plug
HIEC/6	6 way horizontal IEC C13 PDU with switch to 3m lead UK plug
HIEC/8	8 way horizontal IEC C13 PDU with switch to 3m lead, UK plug
HIEC/10	10 way horizontal IEC C13 PDU with switch to 3m lead, UK plug
HIEC/12	12 way horizontal IEC C13 PDU with switch to 3m lead, UK plug

PDU options



IEC C14 plug IEC 320



16A commando plug **IEC 309**



IEC C20 plug IEC 320



Schuko/French CEE 7/7

PDU technical data

0 000	. 20 100		
Weight of PDU	1.1kg – 1.2kg		
Net length of PDU	490mm		
Net width of PDU	60mm		
Net depth of PDU	45mm		
Shipping length of PDU	520mm		
Shipping Width of PDU	132mm		
Shipping Depth of PDU	75mm		
Shipping Weight of PDU	1.3kg – 1.4kg		
PDU max power	3250W		
Output rating	10A		
Overall rating	16A		
Input Frequency	50/60Hz		
Acceptable Input Voltage	250VAC		