

CAT 6A S/FTP Patch Cable

FDL CODE: 4800-XXX



CAT 6A S-FTP patch cable, Cu, LSZH AWG 26/7

The FDL Category 6A Class EA patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 A specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of FDL Category 6A cabling. The performance is tested up to 500 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). FDL patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 6A, because of the transparent yellow colored connector .

Future-oriented standards and high-end quality for your network.

- 2x RJ45 (8P8C) connectors
- Boots with kink protection, strain relief and latch protection
- Length marking on boot
- Conductor: Copper (Cu)
- Assortment: Twisted Pair Patch Cables
- Configuration: 1:1
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Category: CAT.6A
- Shielding: S-FTP, pairs in metal foil and braid shielding
- Length: Various - From 0.25M to 20M
- Color: Various - Grey, Blue, Green, Red, Yellow & More
- Jacket: LSOH
- Structure: 4 x 2 AWG 26/7, twisted pair



