


# **DIGITUS® Modular Couplers, unshielded**







## **Abstract**

DIGITUS® Modular Couplers, unshielded, RJ12 6P6C or RJ45 8P8C

#### **Features**

- 2x RJ jack

Assignment: 1:1Plastic housing

Material PCB: FR4, 1.2 mm thickness
Contacts coating: Nickel, gold plated 0.6 μ

- Mating cycles: ≥ 750

- Operating temperature: -40 °C up to +80 °C

### **Product Overview**

The unshielded modular couplers from DIGITUS® consist of 2 RJ jacks. They are available as RJ12 6P6C or RJ45 8P8C. The assignment is 1:1.

# **Product Number Information**

AT-A 6/6 DIGITUS® Modular Coupler, RJ12, unshielded, 6P6C to 6P6C, color white AT-A 6/6-BL DIGITUS® Modular Coupler, RJ12, unshielded, 6P6C to 6P6C, color black AT-A 8/8 DIGITUS® Modular Coupler, RJ45, unshielded, 8P8C to 8P8C, color white

## **More Modular Adapters**

AT-AG CX2 DIGITUS® CAT 5e Patch cable adapter, shielded, 2x RJ45 jack to 1x RJ45 plug,

cable length 0.19 m, assignment 1:1

DN-93904 DIGITUS® CAT 5e Patch cable adapter, shielded, 2x RJ45 jack to 1x RJ45 plug,

cable length 0.19 m, assignment: 1-1, 2-2, 3-3, 4-1, 5-2, 6-6, 7-3, 8-6

AT-AG 2X8/8 DIGITUS® CAT 5e Modular Coupler, s, 2x RJ45 to 1x RJ45, threefold coupler AT-AG 8/8 C6S DIGITUS® Modular Coupler, 8P8C, 1:1, shielded, CAT6, metal housing

AT-AG6 8/8CROSS DIGITUS® CAT 6 Modular Coupler, shielded, RJ45 to RJ45, crossover version

DN-93901 DIGITUS® CAT 5e Modular Coupler, shielded, RJ45 to RJ45

A-CP-LINK CAT 7 S-FTP RJ45 adapter, shielded, S/FTP AWG27/7 LSZH, pin assignment T568B,

IEC 60603-7-51, color blue