

Modular Plug for Round Cable, CAT 6A, shielded

9200-750



CAT 6A Modular Plug, 8P8C, shielded for Stranded or Solid wire AWG 26-22 - Includes. insert load bar

- 1 Layout performance: CAT 6A, 10GBase-T
- 1 Area of application: Patch cable assembly
- 1 Norms: ISO/IEC 11801 2nd Ed., EN 50173-1, EIA/TIA 568-C
- 1 General properties:
- 1 UL certified
- 1 Technical properties:
- 1 Mating cycles female: > 750 acc. to ISO/IEC 11801, IEC 60603-7-5
- 1 Material connector body: Polycarbonat, clear
- 1 Connector contact: Phosphor bronze, brass 0.6 μ gold-plated
- 1 Flammability: UL 94V-2
- 1 Physical properties:
- 1 Insertion force: \leq 30 N
- 1 Diameter Cu-Conductor: AWG (26/7 - 22/1)
- 1 Operating temperature: -40 °C to +80 °C
- 1 Current carrying capacity: 1A -1.5A at 50 °C





Modular Plug for Round Cable, CAT 6A - Shielded

→ **Logistics**

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	3600	14,34	37,00	51,00	33,00	62271,00
Packaging Unit Inside	100	0,40	23,00	33,00	2,00	1518,00
Packaging Unit Single	1	0,00	1,00	2,00	0,50	1,00
Net single without Packaging	1	0,00	0,00	0,00	0,00	0,00